SANWOOD
environmental test chambers

HIGH TEMPERATURE OVEN



Mobile phone scan
More product information

Energy Conservation



Remote network system



Circuit System



SANWOOD
environment test chamber

● Specifications

Model		SM-G-1000-DA	SM-G-1800-DA	SM-G-2520-DA	SM-G-3600-DA	SM-G-5000-DA	SM-G-8000-DA
Temperature	Temperature range	RT℃～300℃ （A:25℃～200℃;B：25℃～300℃；）					
	Temperature fluctuation	±0.5℃					
	Heating rate	25.0℃～100.0℃ within 8 mins 6.0～10.0℃/min					
	Temperature uniformity	±2.0℃ (25.0℃～100.0℃)					
		±2.5℃ (100.1℃～200.0℃)					
Material	Internal material	Adopts 1.2mm thickness stainess steel(SUS304)					
	External material	Adopts 1.2mm thickness Cold rolled steel sheet / powder spraying					
	Heat insulating material	100mm thickness mineral wool					
	Fan	Centrifugal blower					
	Heater	Nickel chromium alloy heating wire					
Size	Inner size(mm) W*H*D	1000*1000*1000	1000*1500*1200	1200*1500*1400	1200*2000*1500	1500*1800*1850	2000*2000*2000
	Outer size(mm) W*H*D	1200*1550*1450	1200*2000*1650	1400*2000*1850	1400*2350*1950	1700*2150*2300	2300*2450*2600
	Volume（L）	1000L	1800L	2520L	3600L	5000L	8000L
Power supply		380V AC 50/60Hz					
Controller		Standard: Sou th Korea TEMI -1500 Optional: South Korea TEMI - 2500,South Korea TEMI - 2700					

Sanwood (HK) Industrial Corporation.,limited
Guangdong Sanwood Technology Corporation.,limited

ADD: No.88, Songchang Road, Songbotang , Changping, Dongguan, Guangdong
TEL: +86+769-81182799
FAX: +86+769-82987199
E-mail: info@sanwood.cc
www.sanwood.cc
www.climatic-chambers.com

Mobile phone scan
can visit our official website